



Power: 7.5~132 kW

Air Flow: 1~22 m³/min

Pressure: 6~10 bar.g

Optimized mechanical structural design

- ★ Four-bearing with simple structure
- ★ Compact, small size, and space-saving
- ★ Designed without front cover

Large market coverage

- ★ Cost-effective product line with large market share



Power : 7.5~132 kW

Air Flow : 1~23 m³/min

Pressure : 6~10 bar.g

Performance Data (8 bar.g)

Rated Power (kW)	Model	Driven Speed (rpm)	50Hz		
			Air Flow (m ³ /min)	Shaft Power (kW)	Specific Power (kW/m ³ /min)
7.5	AC-077*	3600	1.00	8.10	8.10
11		5200	1.57	11.02	7.02
11	AC-130	3000	1.87	12.20	6.52
15		3600	2.23	14.45	6.48
15	AC-160E	3000	2.38	14.78	6.21
22	AC-240	3000	3.42	22.04	6.44
30	AC-420S	3000	4.62	29.96	6.50
37	AC-420	3000	6.15	37.81	6.15
45	AC-480R	3000	7.27	45.70	6.29
55	AC-600R	3000	9.10	57.45	6.31
75	AC-780R	3000	11.84	73.03	6.17
90	AC-1030R	3000	15.03	97.10	6.46
110	AC-1200R	3000	18.54	117.26	6.32
132	AC-1450R	3000	21.71	135.79	6.25

* Belt-driven type